

MADE IN GERMANY

Wassermann is a medium-sized, owner-operated company with head office in Hamburg. We design and produce high-quality technical devices in Germany. Our main users are dental laboratories, dental clinics and various industrial areas worldwide.

Why a Wassermann product?

Wassermann products are manufactured from high-quality materials and the proportion of plastics used is intentionally kept as low as possible. Our devices are known for their suitability for daily use, functionality and longevity. As a result, the users place high levels of trust in the Wassermann brand. We feel it is our duty to support our customers on a daily basis when it comes to safety, service and productivity. Technological perfection, optimum quality and especially sustainability are the benchmarks we set. Thanks to the combination of these values, the family-owned company, since its establishment in 1927, has gained worldwide recognition as a manufacturer of high-quality products.



Polyquick 260, also suitable for extra large articulators



Self-explanatory symbols, fast and easy operation



Further information are available on our website at www.wassermann.hamburg

Your Dental Dealer

Polyquick 260



Pressure Polymerisation Unit and Compactor



Wassermann Dental-Maschinen GmbH
Rudorffweg 15-17 · 21031 Hamburg · Germany
Phone: +49 (0)40 730 926-0 · Fax: +49 (0)40 730 37 24
info@wassermann-dental.com · www.wassermann.hamburg

Combination Automat

Polyquick 260

Pressure Polymerisation Unit and Compactor

The Polyquick 260 is a pressure polymerisation unit for hot and cold polymerisation of plastics. It can be set to a maximum temperature of 105°C and the polymerisation pressure can be adjusted to a maximum of 5 bar. In automatic mode, the polymerisation time can be preselected up to 99 hours. It has a particularly large pressure pot volume and can hence also accommodate extra large articulators or up to 6 brass flasks including clamp. A touch screen and the newly developed control panel allow the user to set the relevant parameters quickly and easily using self-explanatory symbols. The Polyquick 260 can also be used as a pressure compactor without heating.



Major Features

- Compact table-top unit for pressure polymerisation up to 105°C in a water bath
- Up to three individually configurable polymerisation stages
- The automat can also be operated as a pressure compactor
- Rapid draining: Prompt switch between the two modes
- Separate menu for each mode
- Intelligent workflow preset by the software helps the user to ensure operational safety
- Remaining time displayed to the second
- Powerful, electronically regulated heating for optimal water temperature
- Very large capacity Ø 240 mm, usable depth 160 mm
- Pressure relief valve for protection in case of malfunction (7 bar)
- Engraving in container indicating max. water level
- Time and cost saving due to thermal insulation
- Low maintenance, easy to service
- **Included in delivery:**
 - Flask bracket support
 - Compressed air hose, 2 m
 - Discharge hose, 2 m

| Accessories | Item no. |
|---|---|
| Flask bracket support | 170414 |
| Compressed air hose per meter | 320026 |
| Discharge hose per meter | 320031 |
| On request: flask basket as special accessory | ----- |
| Polyquick 260 | Item no. 170993 |
| Voltage | 220-240 V / 50/60 Hz |
| Power consumption | 4.3 A |
| Output | 1100 W |
| W x H x D | 421 x 437 x 485 mm |
| Weight | 36.8 kg |
| Sound level | ≤ 70 dB (A) |
| Compressed air connection | min. 2 bar |
| Operating pressure | max. 5 bar |
| Pressure chamber | Ø 240 mm, depth 175 mm (usable depth 160 mm) |